80-781

FOAMING DISINFECTANT CLEANER

HMIS RATIN	G
Health	2
Flammability	4
Reactivity	0

MATERIAL SAFETY DATA SHEET

NFPA 704 RAT	ING
Health	2
Flammability	4
Reactivity	0
NFPA 30B LEV	/EL
1	

KIMBALL-MIDWEST
P.O. BOX 2470
COLUMBUS, OH 43216-2470

CORPORATE & EMERGENCY TELEPHONE: 800-424-9300

1	PRODI	ICT	IDEN	ITICIC	MOITA
	PRUII	1(1	11 11-18	1111-10	Δ I II II II II

PART NUMBER	.80-781
PRODUCT NAME	.Foaming Disinfectant Cleaner, EPA Reg
	#11694-34
CHEMICAL FAMILY	.N/A
DOT SHIPPING	.Consumer Commodity ORM-D

$MC^{\dagger}RFDH$	-N12		
OSHA PEL	ACGIHTLV	STEL	%
-	-	-	60-100
-	-	-	3-7
800ppm	800ppm	-	3-7
1000ppm	2500ppm	-	1-5
50ppm	20ppm	-	1-5
-	-	-	1-5
	OSHA PEL - - 800ppm 1000ppm	800ppm 800ppm 1000ppm 2500ppm	OSHA PEL ACGIHTLV STEL

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement. (+=Non-Hazardous Component)

3. PHYSICAL DATA

BOILING POINT (RANGE)	212°F
VAPOR PRESSURE PSIG @ 70°F	70±5
VAPOR DENSITY (AIR = 1)	>1
SOLUBILITY IN WATER	
SPECIFIC GRAVITY (H2O = 1)	
MELTING/FREEZING POINT	
EVAPORATION RATE (Butyl Acetate=1)	
VOC content (by weight)	J ,
APPEARANCE AND ODOR	Clear/Fragrant

4 FIRE AND EXPLOSION DATA

FLASH POINT	N.D.
UPPER EXPLOSIVE LIMIT (%)	N.D.
LOWER EXPLOSIVE LIMIT (%)	N.D.
EXTINGUISHING MEDIA	Not usually necessary as this product does not readily support combustion. Use an extinguishing agent applicable to the fire's fuel source.
SPECIAL FIREFIGHTING PROCEDURES	Keep containers cool and vapors down with water spray. Prevent runoff from entering sewers and public waterways. Wear SCBA in chemical fires.
FIRE AND EXPLOSION HAZARDSheated over 12	
neated over 12	UI.

5. HEALTH FEFECTS DATA

	SHORT TERM	EFFECTS OF	EXPOSURE
--	------------	-------------------	-----------------

ROUTE OF ENTRY...... HEALTH HAZARDS (ACUTE AND CHRONIC).....

...Eyes, Inhalation, Ingestion, Skin

.Causes substantial but temporary eye injury. Harmful if absorbed through the skin. Avoid breathing spray mist. Do not get in eyes, on skin or on clothing. Wear safety glasses or goggles. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse. Contents under pressure. Use good chemical hygiene practices to avoid these hazards.

SIGNS & SYMPTOMS OF

EXPOSURE.....

...Redness, tearing, burning in eyes. Redness, drying of skin. Dizziness, nausea and loss of coordination possible if inadequate ventilation.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

... Preexisting skin & lung disorders may be aggravated by prolonged or repeated occupational overexposure.

5 HEAITH FEFECTS	DATA	(CONT'D)
------------------	------	----------

	FIRST AID PROCEDURES
EYES	Flush with water for at least 15 minutes; obtain medical
	attention
SKIN CONTACT	Wash with soap, large volumes of water; remove
	contaminated clothing
INGESTION	Drink plenty of water. Do not induce vomiting; gastric
	lavage; obtain medical attention
INHALATION	Remove to freshair; seek immediate medical attention; if
	breathing stops, begin artificial respiration; administer
	oxygen: obtain medical attention

SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines)

.. This product contains trace chemicals (Ethylene Oxide and Propylene Oxide) known to the State of California to cause cancer, birth defects and other reproductive harm.

6. REACTIVITY

STABILITY	Stable
INCOMPATIBILITIES	Strong acids and oxidizers.
HAZARDOUS DECOMPOSITION	CO CO nitric acid budrochloric
PRODUCTS	acid & nitrous oxide
HAZARDOUS POLYMERIZATION	Will not occur
HAZARDOUS POLYMERIZATION CONDITIONS	None known

7. PRECAUTIONS FOR SAFE HANDLING & USE

PROTECTIVE EQUIPMENT	
S	afety glasses; NIOSH approved respirator; ventilation ufficient to maintain vapor concentrations below 'LV
	Vash with soap and water before eating, smoking, or ising restroom
e	Jseabsorbentsweeping compound to soak up material; ·liminate all ignition sources; wear protective clothing; blace used absorbent into container
	Dispose of remaining material in accordance with local, tate, and federal guidelines
	itore at temperatures below 120°F; keep away from leat, sparks, or open flame
OTHER PRECAUTIONSV	When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFYTHIS DATA UNDERTHEIR OWN OPERATING CONDITIONS ANDTO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.



Specializing in Materials Management since 1923