

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): Product Division:

ISHINE Janitorial

Product Number: 4055

Spartan Chemical Company, Inc. Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours) 1110 Spartan Drive

Chemical Leak/Spil CHEMTREC 1-(800) 424-9300 (24 hours) Maumee OH 43537

Shipping Description: Buffing, polishing compounds, liquid, n.o.s. **NFPA Ratings: HMIS Ratings: Health:** *1 - Slight; Chronic Hazard Health: 1- Slight Fire: 0 - Minimal Fire: 0 - Minimal Reactivity: 0 - Minimal **Reactivity:** 0 - Minimal Pers. Prot. Equip.: See Section VIII

▼SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

		GAGD :	Table Z- 1 - A			NTP, IARC
Chemical Name(s)	% W	CAS Registry No.	TWA mg/m ³	STEL mg/m ³	CELING mg/m ³	or OSHA Carcinogen
Acrylic polymer	15-20	Proprietary	Not Established	Not Established	Not Established	No
Styrene / Acrylic copolymer	1-5	Proprietary	Not Established	Not Established	Not Established	No
Tributoxyethyl phosphate	1-5	78-51-3	Not Established	Not Established	Not Established	No
Dipropylene glycol methyl ether	1-5	34590-94-8	600 [skin]	909 (ACGIH)	Not Established	No
*Diethylene glycol monoethyl ether	1-5	111-90-0	140 (AIHA)	Not Established	Not Established	No

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point:	212 °F	Vapor Pressure:	Unknown
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Complete
pH:	8.0-9.0	Specific Gravity (H ₂ O=1):	1.037
Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	25-35
Physical State:	Liquid		
Appearance & Odor: Translucent emulsion, ammoniacal odor			

1/7/2009 3:21 PM 1 of 4

▼SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	> 210 °F	Method Used:	ASTM-D56
Flammable Limits:	N/A	Flame Extension:	N/A
Extinguishing Media:	N/A		
Special Fire Fighting Procedures:	N/A		
Unusual Fire & Explosive Hazards:			

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes		
Effects of Overexposure-	Causes mild eye irritation: Symptoms may include pain, redness, swelling and tearing.			
Conditions to Avoid:	May cause skin irritation: Symp	May cause skin irritation: Symptoms may include redness, pain and swelling.		
	Harmful if swallowed: Symptoms may include nausea, vomiting, pain and diarrhea.			
	Inhalation of vapors may cause	respiratory irritation, headache and nausea.		
	Contains diethylene glycol monoethyl ether which may cause central nervous system			
	lepression, liver and kidney impairment.			
	Contains tributoxyethyl phosphate which may cause nervous system effects such as ataxia,			
	_	ors with prolonged or repeated contact.		
	Avoid contact with eyes and skin. Avoid breathing product vapors or mist. Use with			
	adequate ventilation. Do not tas	te or swallow. Wash thoroughly after handling.		
Conditions Aggravated by Use:	Preexisting skin; eye and respirate	ory disorders.		

Emergency & First Aid Procedures:

	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention.
	Remove contaminated clothing. Flush skin thoroughly with plenty of water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.
	Do not induce vomiting unless told to do so by medical personnel. Drink one or two glasses of water to dilute product. Get medical attention. Do not give anything by mouth to an unconscious person.
Inhalation:	Move person to fresh air. If irritation persists get medical attention.

▼SECTION VI: REACTIVITY DATA

Stability:	Stable	Incompatible Materials:	None known
Hazardous Decomposition Products:	None known	Hazardous Polymerization:	Will Not Occur

▼ SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case	Small spills may be flushed with water to sanitary sewer system. Dike and contain large spill
Material is Released or Spilled:	with inert material and transfer liquid to containers for recovery or disposal. Follow all
	federal, state and local regulations. Do not discharge into streams, lakes or other surface
	waters.
Waste Disposal Method:	Incineration or approved landfill.

▼ SECTION VIII: SPECIAL PROTECTION INFORMATION

	Respiratory Protection:	Not usually required when good general	l ventilation is provided. How	ever if exposure levels are
- 11	1	,		I

2 of 4 1/7/2009 3:21 PM

	exceeded (see Section II) or if respiratory irritation occurs, use of a NIOSH approved respirator suitable for the conditions of use and chemicals listed in Section II should be considered.
	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or other impervious gloves are recommended.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further guidance.

3 of 4 1/7/2009 3:21 PM

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Keep from freezing.
Other Precautions:	Keep out of reach of children.

© SCC 06/30/2005 Name: Ronald T. Cook Title: Manager, Regulatory Affairs

ISHINE Effective 06/30/2005 Supercedes: 05/14/2003

Date:

Ref: 29 CFR 1910.1200 (OSHA) Changes: Update Section IX

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.

4 of 4 1/7/2009 3:21 PM